



Cert. No.: MED-B-4301
Job Id.: 344.1-000943-1
Item No.: A.1/3.1

Product description

"DMS Hydromagsil (HDM) 1.3"

composed of HgC12 and synthetic Polymers of density 1.3 kg/m³.

Total thickness 25-50 mm.

Applications/Limitations

Approved for use as primary deck covering, not generating excessive quantities of smoke nor toxic products, throughout the accommodation. Not to be used as an integrated part of a horizontal class A division unless tested as such.

Each product is to be supplied with its manual for installation and use.

Type Examination documentation


Test report: No. PF 10846 Serial No. 7482 dated 16 February 2000 from DIFT, Danish Institute of Fire Technology, Copenhagen, Denmark.

Tested according to IMO FTPC Part 1 (IMO Res. A.799(19)). (Ref. Annex 2 Item 6)

Marking of product

The product or packing is to be marked with name of manufacturer, type designation, MED Mark of Conformity and USCG marking (see below and page 3).

Mark of conformity

The manufacturer is allowed to affix the Mark of Conformity  according to Article 11 in the Council Directive 96/98/EC on Marine Equipment and issue a Declaration of Conformity, only when the module D of Annex B in the same directive is fully complied with.

Module D: The quality system for production and testing shall be approved by the Notified Body.

